

St Marys Type S Masonry Cement

St Marys Masonry Cement - Type S

The St Marys Type S Masonry Cement is a special formulation of St Marys hydraulic cement produced specifically for use in mortar and unit masonry construction.

Specifications

Usage

Recommended for use where higher masonry strength is required, such as for parging, foundation walls and walls designed with reinforcement.

Fyceeds

Standard Chemical and Physical requirements of CSA A3002. Mortars proportioned as per CSA A179 will meet the requirements of that standard.

Available In

 $33^{1}/_{3}$ kg bags

Precautions

Avoid contact with eyes. Contains Portland Cement, which when mixed with water forms a calcium hydroxide solution. If splashed in eyes or skin, flush thoroughly with water. Avoid contact with skin, including contact with saturated clothing. Persistent discomfort requires prompt medical attention. For more information, reference the applicable St Marys Material Safety Data Sheet (MSDS). The MSDS should be consulted prior to use of this product and is available upon request or online at www.stmaryscement.com

Manufacturer

St Marys Cement (Canada) 55 Industrial Street Toronto, Ontario M4G 3W9 Tel.: 416-696-4411

Fax: 416-696-4435 www.stmaryscement.com

Limited Warranty

St Marys warrants that St Marys Type S Masonry cement meets all applicable requirements of CSA A3002.

St Marys makes no warranty, expressed or implied, concerning the product of the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by St Marys Cement, except that the product shall conform to contracted specifications. Due to the lack of control over its use, St Marys will not be responsible for finished work in which St Marys cements are used.